



USE COPPER CONDUCTORS ONLY
SUITABLE FOR AT LEAST 75° C

230/208-50-1
240/220-50-1
PER INVERLATE

L1

L2

COMPONENT CODE	
CC	COMPRESSOR CONTACTOR
COMP	COMPRESSOR
CCAP	DUAL CAPACITOR
DFC	DEFROST CONTROL
DFR	DEFROST RELAY
GRND	EMERGENCY GROUND
HPT	HIGH PRESSURE CONTROL
IBC	INDOOR BLOWER CAPACITOR
IBM	INDOOR BLOWER MOTOR
IBR	INDOOR BLOWER RELAY
LAV	LOW AMBIENT BYPASS CONTROL
LAC	LOW AMBIENT CONTROL
LPB	LOW PRESSURE BYPASS
LFC	LOW PRESSURE CONTROL
LFR	LOW PRESSURE RELAY
PLI	OUTDOOR FAN MOTOR
RV	REG. VALVE SOLenOID
T	TRANSFORMER
VB	TERMINAL BLOCK
VBL	LOW VOLTAGE TERMINAL BLOCK

▲ Labeled wires connect if no options used.

▲ Move red wire to 20V tap for 20V operation

▲ Where applicable

RED (LOW) BLACK (HIGH)

FABRY STD.	FIELD	OPTIONAL
—	—	—
—	—	—
—	—	—
—	—	—

COLOR CODE

	Y	G	B	V
BLACK	Y	G	B	V
BROWN				
RED				
ORANGE				
WHITE				
GRAY				
PINK				
LAVENDER				
SLATE				
TAN				
PINK				
LAVENDER				

HARD WFG. CO.

4066-114 C