



Model	Fan Capacitor
W48G*DC	15 / 370
W60G*DC	N/A

- ⚠ TO CHANGE COOLING BLOWER SPEEDS, SWAP BLUE AND ORANGE WIRES
- ⚠ IF BALANCED CLIMATE IS UTILIZED, THIS WIRE NEEDS TO BE CONNECTED IN CORRELATION WITH THE PURPLE WIRE ON THE BLOWER RELAY

IF ANY ORIGINAL WIRES SUPPLIED WITH THE APPLIANCE MUST BE REPLACED, IT MUST BE REPLACED WITH WIRING MATERIAL HAVING A TEMPERATURE RATING OF AT LEAST 105° C EXCEPT THE IGNITION CABLE WHICH IS 250° C HIGH VOLTAGE CABLE

Same Letter Designated Wires Connect if Option Not Used

- Wire Identification numbers for Bard use only. (99)
- 2 RED - HIGH PRESSURE FAULT
BLUE - LOW PRESSURE FAULT
BLUE FLASH - LOW VOLTAGE

- ⚠ DANGER**
ELECTRICAL SHOCK HAZARD
DISCONNECT POWER BEFORE SERVICING.
- ⚠ WARNING**
USE COPPER CONDUCTORS
ONLY SUITABLE FOR AT LEAST 75° C.

	Factory	Field	Optional
High Voltage			
Low Voltage			