



USE COPPER CONDUCTORS
ONLY SUITABLE FOR AT
LEAST 75° C

C FIELD SUPPLIED VALVES.
MAXIMUM VA LOAD - 8 VA
EACH VALVE

A MOVE RED WIRE TO 208V TAP FOR 208V OPERATION **B** BLACK - HIGH SPEED, RED - LOW SPEED

| COMPONENT CODE | | | |
|----------------|-------------------------|-----|----------------------------|
| CB1 | CIRCUIT BREAKER #1 | IBM | INDOOR BLOWER MOTOR |
| CB2 | CIRCUIT BREAKER #2 | IBR | INDOOR BLOWER RELAY |
| CR1 | CONTROL RELAY #1 | LS | LIMIT SWITCH |
| CR2 | CONTROL RELAY #2 | PL1 | PLUG #1 |
| GND | EQUIPMENT GROUND | T | TRANSFORMER |
| H1 | HEAT STRIP #1 | TB | TERMINAL BLOCK |
| H2 | HEAT STRIP #2 | TBL | LOW VOLTAGE TERMINAL BLOCK |
| HC1 | HEATER CONTACTOR #1 | TCO | THERMAL CUTOFF |
| HC2 | HEATER CONTACTOR #2 | WV1 | WATER VALVE #1 |
| IBC | INDOOR BLOWER CAPACITOR | WV2 | WATER VALVE #2 |

| HIGH VOLTAGE | FACTORY STD. | | | FIELD | | | OPTIONAL | | | COLOR CODE | | | | BARD MFG. CO. | | | | | | | | | | | |
|--------------|--------------|-----|-----|-------|-----|-----|----------|-----|----|------------|---|---|---|---------------|----|----|--------|--------|--------|----|----|-----|------|----------|------------|
| | --- | --- | --- | --- | --- | --- | --- | --- | BK | BR | R | O | Y | | G | BL | W | V (PR) | GY (S) | T | PK | L | TAN | PINK | LAVENDER |
| ACCESSORY | --- | --- | --- | --- | --- | --- | --- | --- | BK | BR | R | O | Y | G | BL | W | V (PR) | GY (S) | T | PK | L | TAN | PINK | LAVENDER | 4095-122 C |