



USE COPPER CONDUCTORS ONLY SUITABLE FOR AT LEAST 75° C

B FIELD SUPPLIED VALVES. MAXIMUM VA LOAD - 8 VA EACH VALVE

A BLACK - HIGH SPEED, RED - LOW SPEED

COMPONENT CODE			
CB1	CIRCUIT BREAKER #1	IBM	INDOOR BLOWER MOTOR
CB2	CIRCUIT BREAKER #2	IBR	INDOOR BLOWER RELAY
CR1	CONTROL RELAY #1	LS	LIMIT SWITCH
CR2	CONTROL RELAY #2	PL1	PLUG #1
GND	EQUIPMENT GROUND	T	TRANSFORMER
H1	HEAT STRIP #1	TB	TERMINAL BLOCK
H2	HEAT STRIP #2	TBL	LOW VOLTAGE TERMINAL BLOCK
HC1	HEATER CONTACTOR #1	TCO	THERMAL CUTOFF
HC2	HEATER CONTACTOR #2	WV1	WATER VALVE #1
IBC	INDOOR BLOWER CAPACITOR	WV2	WATER VALVE #2

	FACTORY STD.	FIELD	OPTIONAL
HIGH VOLTAGE	————	-----	-----
LOW VOLTAGE	————	-----	-----
ACCESSORY	————	-----	-----

COLOR CODE							
BK	BLACK	Y	YELLOW	V	VIOLET	T	TAN
BR	BROWN	G	GREEN	(PR)	PURPLE	PK	PINK
R	RED	BL	BLUE	GY	GRAY	L	LAVENDER
O	ORANGE	W	WHITE	(S)	SLATE		

BARD MFG. CO.
4095-123 C