



USE COPPER CONDUCTORS
ONLY SUITABLE FOR AT
LEAST 75° C

COMPONENT CODE

| | | | |
|------|---------------------------|---------|----------------------------|
| ALR | ALARM RELAY | IBM | INDOOR BLOWER MOTOR |
| CB1 | CIRCUIT BREAKER #1 | IBR | INDOOR BLOWER RELAY |
| CB2 | CIRCUIT BREAKER #2 | LAC | LOW AMBIENT CONTROL |
| CC | COMPRESSOR CONTACTOR | LPC | LOW PRESSURE CONTROL |
| CCM | COMPRESSOR CONTROL MODULE | LS | LIMIT SWITCH |
| COMP | COMPRESSOR | OFC | OUTDOOR FAN CAPACITOR |
| GND | EQUIPMENT GROUND | OFM | OUTDOOR FAN MOTOR |
| H1 | HEAT STRIP #1 | PL1 | PLUG #1 |
| H2 | HEAT STRIP #2 | PM | PHASE MONITOR |
| HC1 | HEATER CONTACTOR #1 | T | TRANSFORMER |
| HC2 | HEATER CONTACTOR #2 | TB, TB2 | TERMINAL BLOCK |
| HPC | HIGH PRESSURE CONTROL | TBL | LOW VOLTAGE TERMINAL BLOCK |
| IBC | INDOOR BLOWER CAPACITOR | TCO | THERMAL CUTOFF |

A , B LABELED WIRES CONNECT IF NO OPTIONS USED.
 C MOVE RED WIRE TO 208V TAP FOR 208V OPERATION
 D RED (LOW) BLACK (HIGH) WERE APPLICABLE
 E (BLACK) HIGH SPEED, NOT TO BE USED ON 50 HZ MODELS

| | FACTORY STD. | FIELD | OPTIONAL |
|--------------|--------------|-------|----------|
| HIGH VOLTAGE | | | |
| LOW VOLTAGE | | | |
| ACCESSORY | | | |

| COLOR CODE | | | | | | | |
|------------|--------|----|--------|------|--------|----|----------|
| BK | BLACK | Y | YELLOW | V | VIOLET | T | TAN |
| BR | BROWN | G | GREEN | (PR) | PURPLE | PK | PINK |
| R | RED | BL | BLUE | GY | GRAY | L | LAVENDER |
| O | ORANGE | W | WHITE | (S) | SLATE | | |

BARD MFG. CO.
4095-229 C