



USE COPPER CONDUCTORS
ONLY SUITABLE FOR AT
LEAST 75° C

| COMPONENT CODE | |
|----------------|----------------------------|
| ALR | INDOOR BLOWER RELAY |
| CB1 | CIRCUIT BREAKER #1 |
| CB2 | CIRCUIT BREAKER #2 |
| CC | COMPRESSOR CONTACTOR |
| CCM | COMPRESSOR CONTROL MODULE |
| COMP | COMPRESSOR |
| GND | EQUIPMENT GROUND |
| H1 | HEAT STRIP #1 |
| H2 | HEAT STRIP #2 |
| HC1 | HEATER CONTACTOR #1 |
| HC2 | HEATER CONTACTOR #2 |
| HPC | HIGH PRESSURE CONTROL |
| IBC | INDOOR BLOWER CAPACITOR |
| IBM | INDOOR BLOWER MOTOR |
| IBR | INDOOR BLOWER RELAY |
| LAC | LOW AMBIENT CONTROL |
| LPC | LOW PRESSURE CONTROL |
| LS | LIMIT SWITCH |
| CCM | COMPRESSOR CONTROL MODULE |
| DFC | OUTDOOR FAN CAPACITOR |
| DFM | OUTDOOR FAN MOTOR |
| PL1 | PLUG #1 |
| PM | PHASE MONITOR |
| T | TRANSFORMER |
| TB, TB2 | TERMINAL BLOCK |
| TBL | LOW VOLTAGE TERMINAL BLOCK |
| TCD | THERMAL CUTOFF |

| Labeled Wires Connect if no Options Used. | |
|---|--|
| △ | HIGH VOLTAGE |
| △ | LOW VOLTAGE |
| △ | ACCESSORY |
| △ | OPTIONAL |
| △ | FACTORY STD. |
| △ | FIELD |
| △ | OPTIONAL |
| △ | RED (LOW) BLACK (HIGH) WERE APPLICABLE |
| BARD MFG. CO. | |
| 4095-318 C | |

| COLOR CODE | |
|------------|----------|
| Y | YELLOW |
| G | GREEN |
| BL | BLUE |
| W | WHITE |
| BK | BLACK |
| BR | BROWN |
| R | RED |
| O | ORANGE |
| V | VIOLET |
| (PR) | PURPLE |
| GY | GRAY |
| (S) | SLATE |
| TAN | TAN |
| PINK | PINK |
| LAVENDER | LAVENDER |