



USE COPPER CONDUCTORS  
ONLY SUITABLE FOR AT  
LEAST 75° C

COMPONENT CODE	COMPONENT CODE
ALR	ALARM RELAY
CB1	CIRCUIT BREAKER #1
CB2	CIRCUIT BREAKER #2
CC	COMPRESSOR CONTACTOR
CCH	CRANKCASE HEATER
CCM	COMPRESSOR CONTROL MODULE
CHR	CRANKCASE HEAT RELAY
COMP	COMPRESSOR
GND	EQUIPMENT GROUND
H1	HEAT STRIP #1
H2	HEAT STRIP #2
HC1	HEATER CONTACTOR #1
HC2	HEATER CONTACTOR #2
HPC	HIGH PRESSURE CONTROL
IBC	INDOOR BLOWER CAPACITOR
IBM	INDOOR BLOWER MOTOR
IBR	INDOOR BLOWER RELAY
LAC	LOW AMBIENT CONTROL
LPC	LOW PRESSURE CONTROL
LS	LIMIT SWITCH
OPM	OUTDOOR FAN CAPACITOR
OPM	OUTDOOR FAN MOTOR
PL1	PLUG #1
PM	PHASE MONITOR
T	TRANSFORMER
TB, TB2	TERMINAL BLOCK
TBL	LOW VOLTAGE TERMINAL BLOCK
TCD	THERMAL CUTOFF

FACTORY STD.		FIELD		OPTIONAL	
HIGH VOLTAGE	LOW VOLTAGE	ACCESSORY	FACTORY STD.	FIELD	OPTIONAL
---	---	---	---	---	---
---	---	---	---	---	---
---	---	---	---	---	---

  

COLOR CODE		COLOR CODE	
BK	BLACK	Y	YELLOW
BR	BROWN	G	GREEN
R	RED	BL	BLUE
U	ORANGE	W	WHITE
		V	VIOLET
		PR	PURPLE
		GY	GRAY
		(S)	SLATE
		L	LAVENDER
		PK	PINK
		TAN	TAN

  

RED (LOW) BLACK (HIGH) WERE APPLICABLE	<b>BARD MFG. CO.</b>
	4095-320 B