



USE COPPER CONDUCTORS
ONLY SUITABLE FOR AT
LEAST 75° C

COMPONENT CODE			
CC	COMPRESSOR CONTACTOR	LPB	LOW PRESSURE BYPASS
CCH	COMPRESSOR CRANKCASE HEATER	LPC	LOW PRESSURE CONTROL
CHR	CRANKCASE HEATER RELAY	LS	LIMIT SWITCH
COMP	COMPRESSOR	OFC	OUTDOOR FAN CAPACITOR
GND	EQUIPMENT GROUND	OFM	OUTDOOR FAN MOTOR
H1	HEAT STRIP #1	PD	PULL DISCONNECT
H2	HEAT STRIP #2	PL1	PLUG #1
HC1	HEATER CONTACTOR #1	T	TRANSFORMER
HC2	HEATER CONTACTOR #2	TB	TERMINAL BLOCK
HPC	HIGH PRESSURE CONTROL	TBL	LOW VOLTAGE TERMINAL BLOCK
IBC	INDOOR BLOWER CAPACITOR	TCO	THERMAL CUTOFF
IBM	INDOOR BLOWER MOTOR	TDR	TIME DELAY RELAY
IBR	INDOOR BLOWER RELAY		
LOR	LOCK OUT RELAY		

▲ LABELED WIRES CONNECT IF NO OPTIONS USED. ▲ RED (LOW) BLACK (HIGH) ▲ MOVE RED WIRE TO 208V TAP FOR 380V OPERATION ▲ (BLACK) HIGH SPEED TAP NOT TO BE USED ON 50HZ MODELS

HIGH VOLTAGE	FACTORY STD.	FIELD	OPTIONAL	COLOR CODE							
				BK	BLACK	Y	YELLOW	V	VIOLET	T	TAN
BR	BROWN	G	GREEN	(PR)	PURPLE	PK	PINK	4095-616 A			
R	RED	BL	BLUE	GY	GRAY	L	LAVENDER				
O	ORANGE	W	WHITE	(S)	SLATE						

